

1660 WX2 WAX REMOVER



DESCRIPTION	Water-based wax remover
SPECIFICATIONS	Easily removes protective film from waxed floors Safe on all types of hard, water-resistant floors Low-foaming product for easier application
HOW TO USE AND DOSING	Dilute product in water according to instructions. Spread over surface to be cleaned with a cloth, mop or scrubber-dryer. No need to rinse. DOSING: 50-150 ml/L (5-15 caps per 5 litres) according to degree of soil.
SPECIFICATION	Appearance: Transparent yellow liquid pH: 11.0 +/- 0.5 Specific weight [g/ml]: 0.970 +/- 0.020 The data given above are typical manufacturing values and not a specification.
PRODUCT COMPATIBILITY	If in doubt, test material compatibility on a small concealed part before use. Immediately remove splashes from alkali-sensitive floors (e.g. wood skirting boards, lacquered or varnished surfaces) with a damp cloth.
USE & STORAGE PRECAUTIONS	The product is formulated for professional use only. Store in original containers. Avoid extreme temperatures. Consult safety sheet for further information on use and disposal.
CERTIFICATIONS/ CONFORMITY	The surfactants contained in this product are biodegradable according to the criteria defined by Regulation (EC) 648/2004 and subsequent amendments.
CHEMICAL COMPOSITION	Consult safety sheet for further information on product ingredients.



**PROFESSIONAL
ACADEMY**



Discover further
informations on your
smartphone.



PALLETIZATION	CODE	1660	EAN	8032680391316		
	Pcs x Box	2	Volume L	5	Fl. Oz.	169,07
	Box x Layer	18	Peso Kg	4,85	Oz.	171,08
	Box x Pit	72				

WWW.SANITECITALIA.COM

LAST UPDATE: 15/02/2021

REV.00/2021